

PT043-WSTM0



Display	Size	4.3" diagonal (16:9)
	Max. Resolution	480 x 272
	Type	TFT LCD
	Max. Colors	TFT True Color ; 65536 Colori
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	500
	Luminance (cd/m2)	400
	Operation	RTOS
	Touch Panel	4 Wire Analog Touch Panel
	CPU	CPU RISC ARM 32Bit 200MHz
	Backup SRAM	128 KB
	Working Memory	32 MB
	Built-in Storage	8 MB (128 MB - Opzionale)
	Real Time Clock (RTC)	Yes
Communication Interface	Micro-SD Slot	Yes
	USB Client	Yes
	USB Host	Yes
	Serial	COM1 RS232/RS422/RS485 - (COM2 RS232/RS485 - Opzionale) COM3 RS232
	Ethernet	N.A
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	5W
Environment	Operating Temperature	0°~50°
	Relative Humidity	10%~90%
	Ingress Protection	IP66
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	130.0 x 106.2 x 39
	Cutout Dimension WxH (mm)	119.0 x 93.0
	Net Weight (kg)	0.33 KG