

## PT070-WST4B



<b>Display</b>	Size	7" diagonal (16 : 9)
	Max. Resolution	800 x 480
	Type	TFT LCD
	Max. Colors	TFT True Color ; 65536 Colori
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	500
	Luminance (cd/m2)	300
	Operation	RTOS
	Touch Panel	4 Wire Analog Touch Panel
	CPU	CPU RISC ARM 32Bit 200MHz
	Backup SRAM	128 KB
	Working Memory	64 MB
	Built-in Storage	8 MB (NOR Flash) + 128 MB (NAND Flash)
	Real Time Clock (RTC)	Yes
<b>Communication Interface</b>	Micro-SD Slot	Yes
	USB Client	Yes
	USB Host	Yes
	Serial	<b>COM1</b> RS232/RS422/RS485
		<b>COM2</b> RS232/RS485
<b>COM3</b> RS232		
Ethernet	YES(10/100Mbps)	
<b>Power</b>	Supply Voltage	24VDC±10% Isolated
	Consumption	15W
<b>Environment</b>	Operating Temperature	0°~50°
	Relative Humidity	10%~90%
	Ingress Protection	IP66
	Cooling	Natural Cooling
<b>Dimension</b>	Dimension WxHxD (mm)	188.0 x 143.3 x 36.1
	Cutout Dimension WxH (mm)	175.0 x 132.6
	Net Weight (kg)	0.6 KG